

# DSI ONE™

**DSI ONE** is a multi-purpose, non-melting EP grease with Molybdenum friction reducer. **DSI ONE** is designed to extend equipment life. Versatile applications meet all low and high temperature operation requirements.

- Optimum performance range is -30° to 500°F (34° to 260°C)
- Withstands up to 500,000 p.s.i. pressure
- One grease for virtually all applications
- Energy savings through friction reduction
- Reduced grease consumption
- Extended equipment life



**High temperature,  
multi-purpose,  
excellent EP protection,  
moly fortified,  
anti-wear,  
anti-rust grease.**

**DSI ONE** meets and exceeds all lubrication requirements set forth by all the following institutions:

**American Gear Manufacturing Association (A.G.M.A.)**

**American Petroleum Institute (A.P.I.)**

**American Society of Testing and Materials (A.S.T.M.)**

**National Lubricating Grease Institute (N.L.G.I.)**

**Society of Automotive Engineers (S.A.E.)**

**Society of Tribologists and Lubrication Engineers (S.T.L.E.)**

Additional technical information available on request.

TEST METHOD	DESCRIPTION	SPECIFICATIONS
	NLGI GRADE	2
ASTM D 217	CONE PENETRATION @ 77°F, WORKED 60 STROKES	265-295
ASTM D 128	THICKENER TYPE	INORGANIC CLAY
ASTM D 128	THICKENER CONTENT, %	6-9
ASTM D 2265	DROPPING POINT, °F	500
ASTM D 445	BASE OIL VISCOSITY SUS @ 40°C	1100-1400
ASTM D 2270	VISCOSITY INDEX	50
VISUAL	COLOR	BLUE
VISUAL	APPEARANCE	SMOOTH
ASTM D 128	MOLYBDENUM DISULFIDE % MIN	1-0

