



**SKIN PROTECTION:** As with any hydrocarbon product, oil-impervious clothing is recommended to prevent skin contact.

**RESPIRATORY PROTECTION:** Use MSHA/NIOSH approved equipment when working in areas of heavy oil mist. Ventilation can be used to control or reduce airborne concentrations of oil.

#### **ENVIRONMENTAL AND DISPOSAL INFORMATION**

**SPILL OR RELEASE TO THE ENVIRONMENT:** Combine and recover any free liquid. There is no CERCLA reportable quantity of OptiCool fluid. With small spills, absorb the fluid with sand or clay absorbent, then flush the area with water. With large spills, contain its flow. A spill of any hydrocarbon fluid to navigable waters that causes a sheen upon the water's surface must be reported immediately to the Coast Guard National Response Center (800-424-8802). Failure to report may result in civil or criminal penalties.

**WASTE DISPOSAL:** OptiCool fluid, when discarded or disposed, is not listed as a hazardous waste per 40 CFR 261.33.

**HANDLING AND STORAGE:** Avoid extremes of temperature in storage. Store OptiCool fluid in tightly closed containers in cool, dry, isolated and well ventilated areas, away from sources of ignition or heat. Store drums on their sides so that bungs are below internal liquid level. Do not store in unlabeled containers.

This Material Safety Data Sheet has been prepared in order to help the users of OptiCool fluid. The data contained herein is believed to be accurate, but no guarantees are given with regard to fitness of use in a particular situation.

Effective Date: July 1, 2005

Completed by David Sundin, Ph.D.